

OCTG

API Casing

Dimensions, Weights and End Finish																			
Outside Diameter		Nominal Weights T&C		Nominal Weights Plain-end		Wall Thickness		Type of Finish Grade								Coupling OD	Thread Type		
In.	mm.	lb/ft.	Kg/mtr	lb/ft.	Kg/mtr	In.	mm.	H-40	J-55 K-55	M65	L-80 R-95	N-80 Type-1,Q	C-90 T-95	C-110	P-110	Q-125	mm	STC LTC	BTC
4½	114.30	9.50	14.14	9.42	14.02	0.205	5.21	PS	PS	PS	-	-	-	-	-	-	127.00	8	-
4½	114.30	10.50	15.63	10.24	15.24	0.224	5.69	-	PSB	PSB	-	-	-	-	-	-	127.00	8	5
4½	114.30	11.60	17.26	11.36	16.91	0.250	6.35	-	PSLB	PLB	PLB	PLB	PLB	P	PLB	-	127.00	8	5
4½	114.30	13.50	20.09	13.06	19.44	0.290	7.37	-	-	PLB	PLB	PLB	PLB	P	PLB	-	127.00	8	5
4½	114.30	15.10	22.47	15.00	22.32	0.337	8.56	-	-	-	-	-	-	-	PLB	PLB	127.00	8	5
5	127.00	11.50	17.11	11.25	16.74	0.220	5.59	-	PS	PS	-	-	-	-	-	-	141.30	8	-
5	127.00	13.00	19.35	12.85	19.12	0.253	6.43	-	PSLB	PSLB	-	-	-	-	-	-	141.30	8	5
5	127.00	15.00	22.32	14.89	22.16	0.296	7.52	-	PSLB	PLB	PLB	PLB	PLB	P	PLB	-	141.30	8	5
5	127.00	18.00	26.79	17.94	26.70	0.362	9.19	-	-	PLB	PLB	PLB	PLB	P	PLB	PLB	141.30	8	5
5	127.00	21.40	31.85	21.32	31.73	0.437	11.10	-	-	PLB	PLB	PLB	PLB	P	PLB	PLB	141.30	8	5
5	127.00	23.20	34.53	23.11	34.39	0.478	12.14	-	-	-	PLB	PLB	PLB	P	PLB	PLB	141.30	8	5
5	127.00	24.10	35.87	24.05	35.80	0.500	12.70	-	-	-	PLB	PLB	PLB	P	PLB	PLB	141.30	8	5
5½	139.70	14.00	20.84	13.72	20.41	0.244	6.20	PS	PS	PS	-	-	-	-	-	-	153.67	8	-
5½	139.70	15.50	23.07	15.35	22.85	0.275	6.98	-	PSLB	PSLB	-	-	-	-	-	-	153.67	8	5
5½	139.70	17.00	25.30	16.88	25.13	0.304	7.72	-	PSLB	PLB	PLB	PLB	PLB	P	PLB	-	153.67	8	5
5½	139.70	20.00	29.76	19.83	29.52	0.361	9.17	-	-	PLB	PLB	PLB	PLB	P	PLB	-	153.67	8	5
5½	139.70	23.00	34.23	22.56	33.57	0.415	10.54	-	-	PLB	PLB	PLB	PLB	P	PLB	PLB	153.67	8	5
5½	139.70	26.80	39.88	26.73	39.78	0.500	12.70	-	-	-	-	-	P	P	-	-	-	-	-
5½	139.70	29.70	44.20	29.66	44.14	0.562	14.27	-	-	-	-	-	P	P	-	-	-	-	-
5½	139.70	32.60	48.52	32.58	48.49	0.625	15.88	-	-	-	-	-	P	P	-	-	-	-	-
6%	168.28	20.00	29.76	19.52	29.06	0.288	7.32	PS	PSLB	PSLB	-	-	-	-	-	-	187.71	8	5
6%	168.28	24.00	35.72	23.61	35.13	0.352	8.94	-	PSLB	PLB	PLB	PLB	PLB	P	PLB	-	187.71	8	5
6%	168.28	28.00	41.67	27.67	41.18	0.417	10.59	-	-	PLB	PLB	PLB	PLB	P	PLB	-	187.71	8	5
6%	168.28	32.00	47.62	31.22	46.46	0.475	12.06	-	-	-	PLB	PLB	PLB	P	PLB	PLB	187.71	8	5
7	177.80	20.00	29.76	19.57	29.12	0.272	6.91	PS	PS	PS	-	-	-	-	-	-	200.03	8	-
7	177.80	23.00	34.23	22.64	33.70	0.317	8.05	-	PSLB	PLB	PLB	PLB	PLB	-	-	-	200.03	8	5
7	177.80	26.00	38.69	25.68	38.21	0.362	9.19	-	PSLB	PLB	PLB	PLB	PLB	P	PLB	-	200.03	8	5
7	177.80	29.00	43.16	28.75	42.78	0.408	10.36	-	-	PLB	PLB	PLB	PLB	P	PLB	-	200.03	8	5
7	177.80	32.00	47.62	31.72	47.20	0.453	11.51	-	-	PLB	PLB	PLB	PLB	P	PLB	-	200.03	8	5
7	177.80	35.00	52.09	34.62	51.52	0.498	12.65	-	-	-	PLB	PLB	PLB	P	PLB	PLB	200.03	8	5
7	177.80	38.00	56.55	37.30	55.52	0.540	13.72	-	-	-	PLB	PLB	PLB	P	PLB	PLB	200.03	8	5
7%	193.68	24.00	35.72	23.49	34.96	0.300	7.62	PS	-	-	-	-	-	-	-	-	215.90	8	-
7%	193.68	26.40	39.29	25.59	38.08	0.328	8.33	-	PSLB	PSLB	PLB	PLB	PLB	P	-	-	215.90	8	5
7%	193.68	29.70	44.20	29.05	43.24	0.375	9.52	-	-	PLB	PLB	PLB	PLB	P	PLB	-	215.90	8	5
7%	193.68	33.70	50.15	33.07	49.22	0.430	10.92	-	-	PLB	PLB	PLB	PLB	P	PLB	-	215.90	8	5
7%	193.68	39.00	58.04	38.09	56.68	0.500	12.70	-	-	-	PLB	PLB	PLB	P	PLB	PLB	215.90	8	5
7%	193.68	42.80	63.70	42.43	63.14	0.562	14.27	-	-	-	PLB	PLB	PLB	P	PLB	PLB	215.90	8	5
7%	193.68	45.30	67.42	44.71	66.54	0.595	15.11	-	-	-	PLB	PLB	PLB	P	PLB	PLB	215.90	8	5
7%	193.68	47.10	70.10	46.79	69.63	0.625	15.88	-	-	-	PLB	PLB	PLB	P	PLB	PLB	215.90	8	5
7¾	196.85	46.10	68.61	45.51	67.72	0.595	15.11	-	-	-	P	P	P	P	P	P	-	-	-
8%	219.08	24.00	35.72	23.61	35.14	0.264	6.71	-	PS	PS	-	-	-	-	-	-	244.48	8	-
8%	219.08	28.00	41.67	27.04	40.24	0.304	7.72	PS	-	PS	-	-	-	-	-	-	244.48	8	-
8%	219.08	32.00	47.62	31.13	46.33	0.352	8.94	PS	PSLB	PSLB	-	-	-	-	-	-	244.48	8	5
8%	219.08	36.00	53.58	35.17	52.35	0.400	10.16	-	PSLB	PSLB	PLB	PLB	PLB	P	-	-	244.48	8	5
8%	219.08	40.00	59.53	39.33	58.53	0.450	11.43	-	-	PLB	PLB	PLB	PLB	P	PLB	-	244.48	8	5

OCTG

API Casing

Dimensions, Weights and End Finish																			
Outside Diameter		Nominal Weights T&C		Nominal Weights Plain-end		Wall Thickness		Type of Finish Grade									Coupling OD	Thread Type	
In.	mm.	lb/ft.	Kg/mtr	lb/ft.	Kg/mtr	In.	mm.	H-40	J-55 K-55	M65	L-80 R-95	N-80 Type-1,Q	C-90 T-95	C-110	P-110	Q-125	mm	STC LTC	BTC
8%	219.08	44.00	65.48	43.43	64.64	0.500	12.70	-	-	-	PLB	PLB	PLB	P	PLB	-	244.48	8	5
8%	219.08	49.00	72.92	48.05	71.51	0.557	14.15a	-	-	-	PLB	PLB	PLB	P	PLB	PLB	244.48	8	5
9%	244.48	32.30	48.07	31.05	46.20	0.312	7.92	PS	-	-	-	-	-	-	-	-	269.88	8	-
9%	244.48	36.00	53.58	34.89	51.93	0.352	8.94	PS	PSLB	PSLB	-	-	-	-	-	-	269.88	8	5
9%	244.48	40.00	59.53	38.97	57.99	0.395	10.03	-	PSLB	PSLB	PLB	PLB	PLB	P	-	-	269.88	8	5
9%	244.48	43.50	64.74	42.74	63.61	0.435	11.05	-	-	PLB	PLB	PLB	PLB	P	PLB	-	269.88	8	5
9%	244.48	47.00	69.95	46.19	68.75	0.472	11.99	-	-	PLB	PLB	PLB	PLB	P	PLB	PLB	269.88	8	5
9%	244.48	53.50	79.62	52.90	78.72	0.545	13.84	-	-	-	PLB	PLB	PLB	P	PLB	PLB	269.88	8	5
9%	244.48	58.40	86.91	57.43	85.47	0.595	15.11	-	-	-	PLB	PLB	PLB	P	PLB	PLB	269.88	8	5
10¾	273.05	32.75	48.74	31.25	46.50	0.279	7.09	PS	-	-	-	-	-	-	-	-	298.45	8	-
10¾	273.05	40.50	60.27	38.92	57.91	0.350	8.89	PS	PSB	PSB	-	-	-	-	-	-	298.45	8	5
10¾	273.05	45.50	67.71	44.26	65.87	0.400	10.16	-	PSB	PSB	-	-	-	-	-	-	298.45	8	5
10¾	273.05	51.00	75.90	49.55	73.75	0.450	11.43	-	PSB	PSB	PSB	PSB	PSB	P	PSB	-	298.45	8	5
10¾	273.05	55.50	82.60	54.26	80.75	0.495	12.57	-	-	PSB	PSB	PSB	PSB	P	PSB	-	298.45	8	5
10¾	273.05	60.70	90.33	59.45	88.47	0.545	13.84	-	-	-	-	-	PSB	P	PSB	PSB	298.45	8	5
10¾	273.05	65.70	97.78	64.59	96.12	0.595	15.11	-	-	-	-	-	PSB	P	PSB	PSB	298.45	8	5
11¾	298.45	42.00	62.51	40.65	60.50	0.333	8.46	PS	-	-	-	-	-	-	-	-	323.85	8	-
11¾	298.45	47.00	69.95	45.63	67.90	0.375	9.53	-	PSB	PSB	-	-	-	-	-	-	323.85	8	5
11¾	298.45	54.00	80.36	52.63	78.32	0.435	11.05	-	PSB	PSB	-	-	-	-	-	-	323.85	8	5
11¾	298.45	60.00	89.29	58.87	87.61	0.489	12.42	-	PSB	PSB	PSB	PSB	PSB	P	PSB	PSB	323.85	8	5
11¾	298.45	65.00	96.73	64.02	95.27	0.534	13.56	-	-	-	P	P	P	P	P	P	-	-	-
11¾	298.45	71.00	105.66	69.48	103.40	0.582	14.78	-	-	-	P	P	P	P	P	P	-	-	-
13%	339.72	48.00	71.43	46.01	68.48	0.330	8.38	PS	-	-	-	-	-	-	-	-	365.12	8	-
13%	339.72	54.50	81.11	52.78	78.55	0.380	9.65	-	PSB	PSB	-	-	-	-	-	-	365.12	8	5
13%	339.72	61.00	90.78	59.50	88.55	0.430	10.92	-	PSB	PSB	-	-	-	-	-	-	365.12	8	5
13%	339.72	68.00	101.20	66.16	98.46	0.480	12.19	-	PSB	PSB	PSB	PSB	PSB	P	PSB	-	365.12	8	5
13%	339.72	72.00	107.15	70.70	105.21	0.514	13.06	-	-	-	PSB	PSB	PSB	P	PSB	PSB	365.12	8	5